

SCHEDULE OF LUMINAIRES

1398 COLEFORD CLOCK TOWER

LED luminaires should be complete with manufacturer's recommended driver or similar. Unless noted otherwise, lamps shall be sourced from the same manufacturer and shall be colour temperature 4000k. For lighting locations please refer to drawings 1398 (10)02 Floor Plans as Proposed and 1398 (13)01 Reflected Ceiling Plans. All lighting to be on individual controls located in the ground floor services cupboard.

Ref.	Type	Size (mm)	Lamp Watts/ Type	Mounting	Manufacturer	Range	Product Code	Details	Image (Indicative for Information Only)
P1	Suspended porch pendant light	H: 450mm, W: 350mm,	4W LED, IP 44	Ceiling surface-mounted	Pooky Lighting	Majorelle IP44 Pendant	PLMAJ100IROBRA	Brass finish, 5.8kg with 600mm minimum drop from the ceiling and 110mmø ceiling rose. 4nr. E14 bulb type to be used	

F1	Recessed floor uplighting	H: 83mm W:ø76mm	2W LED, 208lm, IP68	Floor surface-mounted	Collingwood Lighting	GL040 Ultra Low Glare	GL040AMBL30	Antique brass finish, 3000K, 34 degree angle beam. Installation tube (Tube/68) and IP68 boxes (JB2/ JB4/ JB6) sold separately
----	---------------------------	-----------------	---------------------	-----------------------	----------------------	-----------------------	-------------	---




W1	Up and down wall lights	H: 123mm W:153mm D:96mm	13W LED, IP66	Wall surface-mounted	iGuzzini	Allure 120x150 MM	S667.01 White X800.M5 - Urban Glossy Bronze	AS/ AS: Asymmetrical Side Up Light - Asymmetrical Side Down Light Optic, White 01 finish, with on/off control. Guard with visible border made of polycarbonate for Allure 120x150 MM in Glossy Urban Bronze finish, 3000K, wall arm mounting	
H1	Integrated LED handrail	D: ø42.4mm	9.6W LED, 54lm, IP40	Wall-mounted brackets	The Light Lab	Glowrail 42	As attached quotation	AM Aged Bronze stainless steel finish, 3000K, with 4no. Wall mounted brackets, one illuminated run @ 4m with 2no., elevation changes at the top and bottom of the handrail. Power supply to be fed to bracket via the first floor void. Refer to drawing 1398 (50)02 Internal Stair Handrail Schedule.	
P2	Tubular suspended pendant lights	H: 600mm ø100mm	D: 15W LED	Ceiling surface- mounted	Il Fanale	Girasoli Indoor ø100mm	208.35.ON	Natural brass finish, E27 light bulb with maximum 2000mm drop from the ceiling, with ø110mm ceiling rose	

P3	Tubular suspended pendant lights	H: 400mm ø60mm	D: 5W LED	Ceiling surface-mounted	Il Fanale	Girasoli Indoor ø60mm 208.33.N1	Natural brass finish, GU10 light bulb with maximum 2300mm drop from the ceiling, with ø80mm ceiling rose
----	----------------------------------	-------------------	-----------	-------------------------	-----------	---------------------------------	--



CCR1	Conduit ceiling rose system	H: 100mm. ø100mm	D: IP20	Wall surface-mounted	Jim Lawrence	20mm Conduit Ceiling Rose with BC lamp holder	8011AB	Antique brass finish and for use with BC (B22) LED Soft Coil Vintage GLS bulb (code: BULBBCLEDCG0VT).
------	-----------------------------	---------------------	---------	----------------------	--------------	---	--------	---



CS1	Universal Conduit System	D: ø20mm	N/A	Surface-mounted	Jim Lawrence	Universal Conduit	800901AB - 1m 800802AB - 2m	Antique brass finish and available in 1 and 2m lengths and includes brass tube, 2 x conduit connectors, 2 x 'O' rings and 2 x conduit brackets and fixing screws. Couplers, straight joins, elbows, adaptors, T-junction boxes, 4-way junction boxes, gable gland and additional brackets available separately. Allow for oak bobbins where required to provide spacers between external wall and conduit.
-----	--------------------------	----------	-----	-----------------	--------------	-------------------	--------------------------------	--

